









- F/E** FIRE EXIT
- FFA** ACCESS FOR FIRE AND RESCUE SERVICE PERSONNEL
- FD60s** SELF-CLOSING FIRE DOOR WITH MEDIUM FIRE RESISTANCE DURATION C/W SMOKE SEALS.
- FD30s** SELF-CLOSING FIRE DOOR WITH SHORT FIRE RESISTANCE DURATION C/W SMOKE SEALS.
- V** SMOKE VENT [ 1m<sup>2</sup> MINIMUM ]
-  700mm x 1200mm TEMPORARY WAITING SPACE C/W AN EMERGENCY VOICE COMMUNICATION [ EVC ]
-  POINT OF ORIGIN
-  POINT OF DIVERGENCE
-  MORE THAN 1 DIRECTION OF TRAVEL TO PROTECTED DOOR [ S1 = STAIR 1 / S2 = STAIR 2 ]
-  1 DIRECTION OF TRAVEL TO PROTECTED DOOR OR TO POINT OF DIVERGENCE
-  PLACE OF SPECIAL FIRE RISK
-  FIRE ESCAPE STAIRS / PROTECTED ZONES  
MAXIMUM OCCUPANCY CAPACITY: 296  
APPROPRIATE CAPACITY: 296 x 0.8 = 236

Proposed First Floor Plan - Scheme G

1:100@A2

Drawing No. 4080-SD-G-301-



FOR INFORMATION